

## **Getac S410 G2 Performance 14''/i5-8250U/4GB/500GB/W10P**

**Intel® Core™ i5-8250U (non-vPro) / 14 "TFT / 4GB RAM / 500GB HDD / 4th USB / Membrane Keyboard / 802.11ac Wireless / Bluetooth 4.2 / Windows 10 Pre 64bit / SD Card Reader / Main battery (46WH) / TPM 2.0 / -21C Wide Range Temp / Full HD IPS Panel / Sunlight Readable / Capacitive Touchscreen / NVIDIA® GeForce® GTX 950mm 4GB discrete graphic controller / 120W AC adapter**

Nový Getac S410 G2 zdvíha latku v semi-odolnej triede počítačov tým, že je ešte odolnejší, štíhlejší a ľahší ako kedy predtým. Notebook Getac S410 G2 využíva najnovšie technologické inovácie vrátane vylepšeného výkonu procesora, zvýšeného výkonu grafickej karty a mnohých možností, ktoré vám umožní prispôbiť ho podľa vašich potrieb. Getac S410 je výkonný nástroj určený pre profesionálov v akejkoľvek oblasti.

### **ŠPECIFIKÁCIA:**

#### **Operating System:**

Windows 10 Pre

#### **Mobile Computing Platform:**

Intel® Core™ i7 vPro™ Technology

- Intel® Core™ i7-8650U vPro™ Processor 2.6GHz, Max 3.4GHz, with Intel® Turbo Boost Technology

- 4MB Intel® Smart Cache

Intel® Core™ i7 vPro™ Technology

- Intel® Core™ i7-8550U Processor 2.5GHz, Max. 3.1GHz with Intel® Turbo Boost Technology

- 4MB Intel® Smart Cache

Intel® Core™ i5 vPro™ Technology

- Intel® Core™ i5-8350U vPro™ Processor 2.4GHz, Max. 3.0GHz with Intel® Turbo Boost Technology

- 3MB Intel® Smart Cache

Intel® Core™ i5 Technology

- Intel® Core i5-8250U Processor 2.3GHz Max. 2.8GHz with Intel® Turbo Boost Technology

- 3MB Intel® Smart Cache

Intel® Core™ i3 Technology

- Intel® Core i3-7100U Processor 2.3GHz

- 3MB Intel® Smart Cache

#### **VGA Controller:**

Intel® HD Graphics 520

Optional NVIDIA® GeForce® GTX 950mm 4GB discrete graphic controller

#### **Display:**

14 "TFT LCD HD (1366 x 768)

Optional 1000 nits Lumibond® display with Getac sunlight Readable technology Capacitive multi-touch screen

Optional 14 "IPS TFT LCD FHD (1920 x 1080)

Optional 800nits Lumibond® display with Getac sunlight Readable technology Capacitive multi-touch screen

**Storage & Memory:**

4GB LPDDR3 Expandable to 16GB

Main Storage:

SATA HDD 500GB

Optional SATA HDD 1TB

Optional SATA OPAL 2.0 SSD 128GB / 256GB / 512GB / 1TB

Optional 2nd Storage (onboard): 128GB OPAL 2.0 SSD

**Keyboard:**

Membrane keyboard

Optional LED backlit membrane keyboard

**Pointing Device:**

touchscreen

- Optional Capacitive multi-touch screen

touchpad

- Glide touchpad with multi-touch

**Expansion Slots:**

SD card reader x 1

Optional Smart Card reader x 1

**Multimedia Bay:**

Optional PCMCIA Type II

Optional ExpressCard34 / 54

Optional DVD super multi skoršie

Optional 2nd battery

**IO Interface:**

Headphone out / mic-in Combo x 1

DC in Jack x 1

USB 3.0 (9-pin) x 3

USB 2.0 (4-pin) x 1

LAN (RJ45) x 1

HDMI x 1

Docking Connector (16-pin) x 1

Optional Serial port (9-pin; D-sub) x 1

Optional VGA Port (15-pin; D-sub) x 1

Optional SIM Card Slot x 1

Optional FHD webcam x 1

Optional RF antenna pass through for GPS, WWAN and WLAN

Optional Rugged USB 2.0, Rugged LAN,

Optional PowerShare USB 2.0 or LAN (RJ45) x 1

**Communication Interface:**

Intel® Dual Band Wireless-AC 8260, 802.11ac  
Bluetooth (v4.2)  
Optional dedicated GPS  
Optional 4G LTE mobile broadband

**Software:**

Getac Utility  
Adobe® Reader®  
Optional Absolute DDS® Persistence

**Security Features:**

Optional Intel® vPro™ Technology  
TPM 2.0  
Optional fingerprint scanner  
Optional Smart Card reader  
Optional Contactless Smart Card reader  
Kensington lock

**Power:**

AC adapter (65W, 100-240VAC, 50 / 60Hz)  
Optional AC adapter (120W, 100-240VAC, 50 / 60Hz)  
Li-Ion battery (11.1V, 4200mAh)  
(Up to 11 hours of battery life)  
LifeSupport™ battery swappable technology (with optional bridge battery)

**Dimensions & Weight:**

Without Discrete GPU  
350 x 293 x 34.9 mm (13.8 "x 11.5" x 1.4 ")  
2.2kg (4.9lbs)

With Discrete GPU  
350 x 293 x 42.6 mm (13.8 "x 11.5" x 1.7 ")  
2.7kg (5.9lbs)

**Rugged Features:**

MIL-STD-810G certified and IP52 certified  
Splash resistant keyboard  
3 feet drop resistant  
Sealed ports and connectors  
Shock-protected removable HDD  
vibration resistant

**Environmental Specifications:**

temperature:  
- Operating: -21 ° C to 60 ° C / -5.8F to 140 ° F  
- Storage: -51 ° C to 71 ° C / -60 ° F to 160 ° F  
Humidity:  
- 95% RH, non-condensing