

OSADENIE REGULAČNEJ ARMATÚRY NA STÚPAČKACH

	1	2	3	4	5	6	7	8			
160	2.29 20°C 21 K/55160 1 x TS-90 15 1 x RL-5 15	2.29 20°C 22 K/55100 1 x TS-90 15 1 x RL-5 15	2.29 20°C 22 K/55100 1 x TS-90 15 1 x RL-5 15	2.27 20°C 22 K/55100 1 x TS-90 15 1 x RL-5 15	2.26 20°C 21 K/55100 1 x TS-90 15 1 x RL-5 15	2.25 20°C 22 K/55220 1 x TS-90 15 1 x RL-5 15	2.18 20°C 21 K/55060 1 x TS-90 15 1 x RL-5 15	2.23 20°C 21 K/55080 1 x TS-90 15 1 x RL-5 15	2.14 20°C 22 K/55140 1 x TS-90 15 1 x RL-5 15	2.15 20°C 21 K/55140 1 x TS-90 15 1 x RL-5 15	2.11 22°C 22 K/55080 1 x TS-90 15 1 x RL-5 15
3/4"	GU 1" VK 1/2" 1.26	RA 3/4" VK 1/2" 1.26	RA 3/4" VK 1/2" 1.26	RA 3/4" VK 1/2" 1.25	GU 1" VK 1/2" 1.25	RA 3/4" VK 1/2" 1.24	RA 1/2" VK 1/2" 1.18	GU 3/4" VK 1/2" 1.23	RA 3/4" VK 1/2" 1.13	GU 1" VK 1/2" 1.13	20°C
40	2.29 20°C 21 K/55080 1 x TS-90 15 1 x RL-5 15	2.29 20°C 21 K/55080 1 x TS-90 15 1 x RL-5 15	2.29 20°C 21 K/55080 1 x TS-90 15 1 x RL-5 15	2.27 20°C 22 K/55080 1 x TS-90 15 1 x RL-5 15	2.26 20°C 21 K/55080 1 x TS-90 15 1 x RL-5 15	2.25 20°C 22 K/55200 1 x TS-90 15 1 x RL-5 15	2.18 20°C 21 K/55060 1 x TS-90 15 1 x RL-5 15	2.23 20°C 21 K/55080 1 x TS-90 15 1 x RL-5 15	2.14 20°C 22 K/55140 1 x TS-90 15 1 x RL-5 15	2.15 20°C 21 K/55140 1 x TS-90 15 1 x RL-5 15	2.11 22°C 22 K/55080 1 x TS-90 15 1 x RL-5 15
1/2"	GU 1" VK 1/2" 1.26	RA 3/4" VK 1/2" 1.26	RA 3/4" VK 1/2" 1.26	RA 3/4" VK 1/2" 1.25	GU 1" VK 1/2" 1.25	RA 3/4" VK 1/2" 1.24	RA 1/2" VK 1/2" 1.18	GU 3/4" VK 1/2" 1.23	RA 3/4" VK 1/2" 1.13	GU 1" VK 1/2" 1.13	20°C

RA 3/4"
VK 1/2"